

ACO Cablemate®

Exploded view diagram of the Pits™ system components, showing the following parts from top to bottom:

- Top covers:** Two dark grey covers with a grid of circular holes and red locking pins.
- Top tray:** A light grey tray with a grid of rectangular compartments.
- Bottom tray:** A light grey tray with a grid of rectangular compartments.
- Locking lids:** Two light grey lids with a grid of rectangular compartments and red locking pins.
- Lids / Bottom:** A light grey lid with a grid of rectangular compartments.
- The Pits™:** A stack of dark grey rectangular pits.

Note: 1. Risers can be created from polyethylene moulded pits by cutting the base off the pit. For further details refer to the Specification Information sheets. Risers not available for Type 43 and Type 9 pits.
2. If access covers are selected, the pit must be installed below the pavement. For more information, see installation details on www.acocablemate.com.au
3. **Polycrete®** is ACO's trademark for products made from polymer concrete.
4. Designed for 40mm pavers.

Rhinocast®
iron access covers

Urbanfil®
steel access covers

Steel **PowerLock®** lids

Steel non-locking lids

Polycrete®³ lids / concrete lids

Polycrete®³ Pits
with lid and access cover options

Note: 1. If risers are used, add 300mm to the depth. Risers are not available for Type S2 & 63.
2. If access covers are selected, the pit must be installed below the pavement.
For more information, see installation details on www.acocablemate.com.au
3. **Polycrete®** is ACO's trademark for products made from polymer concrete.
4. Designed for 40mm pavers.



EzyBrixx® rigid twin wall plastic pits



www.acocablemate.com.au



Certified System
Quality
ISO 9001

© 2025 ACO Pty Ltd. PO 0004 (A3) PO 0002 (A4) - 2025

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.